


概要

製品情報



15EDGRC-THR-3.5-10030000310

Pluggable terminal blocks, Rated current: 8A. Rated voltage (III/2) : 250V, pitch: 3.5mm, Color: black, Contact surface : Tin

製品の特長

- ☒ Suitable for SMT welding process
- ☒ The plug direction is parallel to the PCB, Can meet the needs of different connectors

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

8A

Electrical parameters IEC

Rated voltage

250V

Rated current

8A

Rated current(III/2)

250V

Rated surge voltage(III/2)

2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~130℃
---------------------------------	-----------

アクセサリ

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

ビジネスデータ	
注文番号	10030000310
パッキングユニット	500
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	0.45