


## 概要

### 製品情報



**15EDGKM-3.81-10010000749**

Pluggable terminal blocks, Rated current: 7A. Rated voltage  
(Ⅱ/2) : 250V, pitch: 3.81mm, Color: green, Contact surface : Tin

### 製品の特長

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Universal installation method, suitable for various situations

### 製品認証



## 技術データ

### 製品チャート

#### 3Dモデル

□

### Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 0.5~1.5mm <sup>2</sup> |
| Conductor cross section flexible | 0.5~1.5mm <sup>2</sup> |
| AWG                              | 28~16AWG               |
| Torque                           | 0.2N.m                 |
| Strip length                     | 7mm                    |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 8A   |

|                   |    |
|-------------------|----|
| Rated current (D) | 8A |
|-------------------|----|

#### Electrical parameters IEC

|                           |       |
|---------------------------|-------|
| Rated voltage             | 250V  |
| Rated current             | 7A    |
| Rated current(II/2)       | 250V  |
| Rated surge voltage(II/2) | 2.5KV |

#### Item properties

|                      |                     |
|----------------------|---------------------|
| Connection direction | 0°                  |
| Connection method    | Screw connection    |
| Screwdriver          | Slotted screwdriver |
| screw thread         | M2                  |
| Pitch                | 3.81mm              |
| Number of potentials | 2                   |
| Pluggable or not     | Yes                 |
| Number of rows       | 1                   |

#### Material data

|                            |                           |
|----------------------------|---------------------------|
| Environmental items        | Compliant with REACH/RoHS |
| Contact material           | Copper alloy              |
| Contact zone metal surface | tin-plated                |
| Insulation Materials       | PA66                      |
| Insulating material group  | I                         |
| Flammability rating        | UL94V-0                   |

#### Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

#### Environmental data

Ambient temperature (operation)

-40℃~105℃

## アクセサリ

### Tool

Screwdriver

0.4x2.5,Slotted screwdriver

Operating tool

/

### Accessories

Coding strip

/

Bridge

DG032-3.81

Marking strip

/

Others

/

## ビジネスデータ

注文番号

10010000749

パッキングユニット

200

最小注文数量

30

1個あたりの重量（梱包を  
含めない）

2.274