


概要

製品情報



15CDGV-3.81-10030000001

Pluggable terminal blocks, Rated current: 7A. Rated voltage
(Ⅱ/2): 250V, pitch: 3.81mm, Color: green, Contact surface: Tin

製品の特長

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Through-wall installation, free positioning

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A
Rated current (D)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	7A

Rated current(II/2)	250V
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	3.81mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Tool

Screwdriver	/
-------------	---

Operating tool	/
----------------	---

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI

ビジネスデータ

注文番号	10030000001
パッキングユニット	100
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	1.375