

概要

製品情報



5EDGVL-7.62-10020003460

Pluggable Terminal Blocks, Rated current: 41A, Rated voltage (III/2) : 630V, Pitch: 7.62mm, Color: Green, Contact surface: Tin

製品の特長

- ☒ Universal installation method to ensure a high degree of flexibility in device design.
- ☒ The plug direction is perpendicular to the PCB.

製品認証



技術データ

製品チャート

3Dモデル

□

Electrical parameters UL

Rated voltage (B)	42A
Rated voltage (C)	42A

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (D)	5A

Electrical parameters IEC

Rated voltage	630V
Rated current(III/3)	500V
Rated current	41A
Rated current(III/2)	630V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Three rows in a straight line
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIb
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ	
Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	2EDG-PWI
Bridge	/
Marking strip	/
Others	/

ビジネスデータ	
注文番号	10020003460
パッキングユニット	360
最小注文数量	
1 個あたりの重量（梱包を 含めない）	6.17