

概要

製品情報

**Bus IO-DF750-HT-001-11-1001A(H)-30050000253**

Card IO housing,push-instructure,Can be matched bring light RJ45Connector,LEDinstruct

製品の特長

- ☑Dual network port without light RJ45 interface
- ☑8-bit address interface
- ☑Internal bus through bottom 6 gold-plated terminals
- ☑Equipped16aislePower Module ,LEDs per node
- ☑Internal 2 gold-plated blade connectors for power cascading expansion
- ☑Can be installed on DIN rail

製品認証

技術データ

製品チャート

3Dモデル

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Mechanical parameters

structure type

Compact terminal module housing with signal LED

Material

PC+PA66

installation

DIN35 rail

Side by side installation

Dovetail groove clamping

label

Laser screen printing

color

C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Dimension

length	100mm
width	48mm
Height	69mm

アクセサリ

ビジネスデータ

注文番号	30050000253
パッキングユニット	20 SKT
最小注文数量	20 SKT
1 個あたりの重量（梱包を 含めない）	122.5g