

概要

製品情報



Relay base-DSRT05A-3-00A(H)-30020000057

DSRTrelay base,used for1PDTrelay,screw connection

製品の特長

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 16A, 1PDTgrade

製品認証

技術データ

製品チャート

3Dモデル

□

Environmental data

Ambient temperature (storage/transport)	-40 °C ... +85 °C
Ambient temperature (operation)	-20 °C ... 50 °C

Technical data

Rated voltage UN	300V
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm

screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	73.3mm
width	16mm
Depth including bracket	29.5mm

アクセサリ

ビジネスデータ

注文番号	30020000057
パッキングユニット	20 SKT
最小注文数量	20 SKT
1 個あたりの重量（梱包を 含めない）	27g