

概要

製品情報



Relay base-DPTF08A-3-00A(H)-30020000053

DPTFrelay base,used for2PDTrelay,screw connection

製品の特長

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 10A, 2PDTgrade
- ☒ Arc partition between adjacent columns

製品認証

技術データ

製品チャート

3Dモデル

□

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

Ambient temperature (storage / transport)	-40~+65℃
---	----------

Technical data

Rated voltage UN	300V
------------------	------

Rated current IN	10A
------------------	-----

Installation location	Arbitrary
-----------------------	-----------

Assembly instructions	DIN35 rail
-----------------------	------------

Connection data 1

Connection name	enter
-----------------	-------

Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	71mm
width	30mm
Depth including bracket	27.5mm

アクセサリ

ビジネスデータ

注文番号	30020000053
パッキングユニット	
最小注文数量	
1 個あたりの重量（梱包を 含めない）	