


概要

製品情報



15EDGRHBN-THR-3.5-10030003294

Pluggable Terminal Blocks nominal current 8A. Rated voltage (II/2): 250V, pitch: 3.5mm, Color: black, Contact surface: Tin

製品の特長

- ☒ Suitable for SMT welding process
- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ Multi-layer wire connection can achieve higher contact density

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Reflow soldering/wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

8A

Rated current (D)

8A

Electrical parameters IEC

Rated voltage

160V

Rated current(III/3)	160V
Rated current	8A
Rated current(III/2)	160V
Rated current(II/2)	250V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	3.5mm
Number of potentials	6
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40℃~130℃

アクセサリ

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

ビジネスデータ

注文番号	10030003294
パッキングユニット	
最小注文数量	
1 個あたりの重量（梱包を 含めない）	