


## 概要

## 製品情報

**15EDGVM-THR-3.5-10030003471**

Pluggable Terminal Blocks  
nominal current 7A, Rated voltage (II/2):  
250V, pitch: 3.5mm, Color: black, Contact surface: Tin

## 製品の特長

- ☑ Suitable for SMT welding process
- ☑ The plug direction is perpendicular to PCB, Can meet the needs of different connectors

## 製品認証



## 技術データ

## 製品チャート

## 3Dモデル

□

## Processing notes

Process

Wave soldering/manual soldering

## Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

8A

## Electrical parameters IEC

Rated voltage

250V

Rated current

8A

Rated current(III/2)

250V

Rated surge voltage(III/2)

2.5KV

Item properties

|                      |                               |
|----------------------|-------------------------------|
| Connection direction | 90°                           |
| Type of installation | PCB welding                   |
| Pin arrangement      | Single row in a straight line |
| Pitch                | 3.5mm                         |
| Number of potentials | 3                             |
| Pluggable or not     | Yes                           |
| Number of rows       | 1                             |

Material data

|                             |                                      |
|-----------------------------|--------------------------------------|
| Environmental items         | Compliant with REACH/RoHS            |
| Contact material            | copper                               |
| Contact point metal surface | tin-plated                           |
| Insulation Materials        | High temperature resistant materials |
| Insulating material group   | IIIa                                 |
| Flammability rating         | UL94V-0                              |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~130℃ |
|---------------------------------|-----------|

アクセサリ

Tool

|                |   |
|----------------|---|
| Screwdriver    | / |
| Operating tool | / |

Accessories

|               |   |
|---------------|---|
| Coding strip  | / |
| Bridge        | / |
| Marking strip | / |
| Others        | / |

ビジネスデータ

|                        |             |
|------------------------|-------------|
| 注文番号                   | 10030003471 |
| パッキングユニット              |             |
| 最小注文数量                 |             |
| 1 個あたりの重量（梱包を<br>含めない） |             |