


## 概要

### 製品情報



### DG25H-B-12020000579

Single layer PCB fence terminal,nominal current15A.Rated voltage(UL): 300V,Rated cross section:22~14AWG,pitch:7.62mm,Color:black,Contact surface:Tin

### 製品の特長

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Solder board installation, which can realize the electrical connection between the device and the PCB

### 製品認証

## 技術データ

### 製品チャート

### 3Dモデル

□

### Connection capacity

|        |          |
|--------|----------|
| AWG    | 22~14AWG |
| Torque | 0.5N.m   |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 15A  |
| Rated current (D) | 10A  |

### Item properties

|                      |             |
|----------------------|-------------|
| Type of installation | PCB welding |
|----------------------|-------------|

|                      |                               |
|----------------------|-------------------------------|
| Pin arrangement      | Single row in a straight line |
| Connection method    | Screw connection              |
| Screwdriver          | Phillips screwdriver          |
| screw thread         | M3                            |
| Pitch                | 7.62mm                        |
| Number of potentials | 4                             |
| Pluggable or not     | no                            |
| Number of rows       | 1                             |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | Copper alloy              |
| Contact point metal surface | tin-plated                |
| Insulating material group   | IIIa                      |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |        |
|--------------------|--------|
| Test Specification | UL1059 |
|--------------------|--------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

アクセサリ

Accessories

|  |  |
|--|--|
|  |  |
|--|--|

ビジネスデータ

|      |             |
|------|-------------|
| 注文番号 | 12020000579 |
|------|-------------|

|                        |       |
|------------------------|-------|
| パッキングユニット              | 460   |
| 最小注文数量                 | /     |
| 1 個あたりの重量（梱包を<br>含めない） | 8.942 |