

概要

製品情報



SA-EBBH-2006-F-00A(H)-25080000002

Charging and discharging receptacle at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance > 500M Ω; Protection grade: IP67 when mated &single.Mechanical life ≥ 3000 cycles; Pull out force > 20N; Working temperature: - 40 ~ 105 °C; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

製品の特長

- ☑ Compact structure and high space utilization
- ☑ Adopt bayonet locking structure to prevent accidental unlocking
- ☑ Direct plug operation, convenient and fast
- ☑ Signal pin No.: 0~8 pins
- ☑ Multiple auditory and visual feedback are inserted in place
- ☑ Beautiful appearance, fit human functional design

製品認証

RoHS

技術データ

製品チャート

3Dモデル

□

Marking

Series	DA
	DD
	DM

versions

Connection method	Crimping connection
Female/Male	Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
	48B
Number of positions	15
	25
	42
パラメーター	
絶縁抵抗	≥500MΩ
機械的寿命	≥3000次
環境条件	
保護等級	MatchingIP67

アクセサリ

ビジネスデータ	
注文番号	25080000002
パッキングユニット	
最小注文数量	
1 個あたりの重量（梱包を 含めない）	