

概要

製品情報



ES-K-350-10090000081

Panel feed-through connectors for energy storage systems, rated current: 350A, rated voltage: 1000V, max cross section: 95mm², copper busbars: 20mm*5mm, color: orange, contact surface: Ni

製品の特長

- ☒ The rotatable cover can effectively avoid the loss or damage of the cover at the construction site
- ☒ The pre cut structure can be flexibly removed according to the site conditions to enhance safety protection;
- ☒ The design of two-way opening can connect the energy storage battery in series or in parallel
- ☒ The product has low temperature rise to realize safe, economical and efficient connection

製品認証

技術データ

製品チャート

3Dモデル

□

Electrical parameters UL

Rated voltage	1000V
Rated current	350A

Connection capacity

Cross section	95mm ²
Copper busbars	20mm*5mm
AWG	3/0AWG

Item properties

Screw thread(front)	M10
Screw thread(behind)	M6

Type of installation	panel
Connection method	Screw connection
Number of potentials	1
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	Nickel plating
Contact zone metal surface	Nickel plating
Insulation Materials	PC
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~125℃
---------------------------------	-----------

アクセサリ

ビジネスデータ

注文番号	10090000081
パッキングユニット	16
最小注文数量	
1 個あたりの重量（梱包を 含めない）	133.8