


## 概要

### 製品情報



### DSIO-IN 2.5/3 OG-11040000239

Power terminals, connector method: Push-in connector, Rated voltage : 250 V, Rated current : 20 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, Width: 7 mm, Color: Orange, Mounting type: NS35/7.5, NS35/15

### 製品の特長

- ☑ Power terminals.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With wire button, one word or cross screwdriver can release wire.
- ☑ Unique plug-in bridge, high circuit connection efficiency.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

### 製品認証



## 技術データ

### 製品チャート

### 3Dモデル

□

### Wiring data

|                                   |                        |
|-----------------------------------|------------------------|
| Strip length                      | 10~12mm                |
| Conductor cross section solid     | 0.2~4mm <sup>2</sup>   |
| Conductor cross section flexible  | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section solid AWG | 26~12                  |

### Environmental conditions

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Ambient temperature (operation) | -40 °C ~ 105 °C (depending on derating curve) |
|---------------------------------|-----------------------------------------------|

|                                       |         |
|---------------------------------------|---------|
| Relative humidity (storage/transport) | 25%~75% |
|---------------------------------------|---------|

#### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 250V |
| Rated surge voltage     | 4KV  |

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

#### Dimension

|                  |        |
|------------------|--------|
| NS 35/7,5 Height | 41.5mm |
| End plate width  | 2.2mm  |
| NS 35/15 Height  | 49mm   |
| width            | 7mm    |
| Height           | 34mm   |

#### Overview

|                                           |                    |
|-------------------------------------------|--------------------|
| Connection type                           | In line connection |
| Number of rows                            | 1                  |
| number of connections                     | 2                  |
| Open-end side panels                      | Yes                |
| Insulation Materials                      | PA                 |
| Flame retardant grade, in line with UL 94 | V0                 |

#### アクセサリ

#### Marker

|             |           |
|-------------|-----------|
| Top marker  | ZB6 / ZS6 |
| Side marker | ZSF6      |

|                                                       |                                       |
|-------------------------------------------------------|---------------------------------------|
| Marker support                                        | DTH5-25x5 / DTH5-25x12                |
| Accessories                                           |                                       |
| Slotted screwdriver size (Blade thickness x Width) mm | 0.6x3.5                               |
| Bridge                                                | DFBXX-3.5                             |
| End cover                                             | D-DSIO1.5/3-1                         |
| Installation                                          |                                       |
| End clamp                                             | E-WS N / E-PC-1100A                   |
| Terminal strip marker support                         | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                                              | NS35/7.5-1000-00A(H)                  |

|                        |             |
|------------------------|-------------|
| ビジネスデータ                |             |
| 注文番号                   | 11040000239 |
| パッキングユニット              | 25          |
| 最小注文数量                 | 25          |
| 1 個あたりの重量（梱包を<br>含めない） | 12.9        |