


概要

製品情報



DS6-QU-PE-11040000146

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.5 mm² - 10 mm², AWG: 20 - 8, Width: 8.2 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

製品の特長

- ☒ Push-in connection technology, tool-free operation, more convenient and faster;
- ☒ With orange wire button, one word or cross screwdriver can release wire.
- ☒ Optional marker to avoid wire mis-inserting.
- ☒ Equipped with test holes for easy testing of the circuit.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length	10~12mm
Conductor cross section solid	0.5~10mm ²
Conductor cross section flexible	0.5~6mm ²
Conductor cross section solid AWG	20~8

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	43.5mm
End plate width	1.5mm
NS 35/15 Height	51mm
width	8.2mm
Height	36mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker	ZB8 / ZS8
Side marker	ZSF8
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.8x4
---	-------

Bridge	/
End cover	D-DS6-QU

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11040000146
パッキングユニット	25
最小注文数量	25
1 個あたりの重量（梱包を 含めない）	29.86