

概要

製品情報



DS4-HE-11040000163

Fuse terminal blocks, connector method: Push-in connector, Fuse type: G / 5 x 20, Glass/ceramic/..., Rated voltage : 400 V, Rated current : 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, Width: 6.2 mm, Color: black, Mounting type: NS35/7.5, NS35/15

製品の特長

- ☒ Fuse terminal blocks.
- ☒ Push-in connection technology, tool-free operation, more convenient and faster;
- ☒ With orange wire button, one word or cross screwdriver can release wire.
- ☒ Snap-on fuse box for easy fuse replacement.
- ☒ Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
- ☒ Equipped with test holes for easy testing of the circuit.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length	11~13mm
Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~4mm ²
Conductor cross section solid AWG	24~10

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
---------------------------------	---

Relative humidity (storage/transport)	25%~75%
---------------------------------------	---------

IEC Electrical parameters

Rated voltage (III / 3)	400V
Rated current (III / 3)	6.3A
Rated surge voltage	6KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	55.6mm
width	6.2mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...

Marker

Top marker	ZB6 / ZS6
Side marker	ZSF6
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
Bridge	DFBXX-6.2
End cover	D-DS4-HE

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11040000163
パッキングユニット	100
最小注文数量	100
1 個あたりの重量（梱包を 含めない）	9.53