


概要

製品情報

**PC50-PE-01A(H)-11010002999**

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 16 mm² - 50 mm², AWG: 6 - 1/0, Width: 20 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

製品の特長

- ☑Screw connection technology, reliable connection;
- ☑Grounding structure, protection circuit;
- ☑Copper alloy material, good corrosion resistance;
- ☑Can be matched with marker strips to avoid incorrect insertion of wires.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Screw type	Allen screws
2 flexible conductors with a TWIN ferrule	10-16mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	16-50mm ²
Conductor cross section flexible (ferrule without plastic sleeve)	16-50mm ²
Strip length	22~23mm
Conductor cross section solid	16~50mm ²
Conductor cross section flexible	16~50mm ²

Conductor cross section solid AWG	6~1/0
screw thread	M6
Tightening torque	2.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	75.95mm
NS 35/15 Height	83.45mm
length	70.45mm
width	20mm
Height	76.1mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Accessories

Slotted screwdriver size (Blade thickness x Width)	Hex key 5mm
Fixed bridge	/
Insertion bridge	/
End cover	/
Separating disk	/
Partition plate	/

Marker

Top marker	/
Marker	ZT12
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

ビジネスデータ

注文番号	11010002999
パッキングユニット	10
最小注文数量	10
1 個あたりの重量（梱包を含めない）	175.484