

概要

製品情報



DC10-TW-11020000206

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 1000 V, Rated current: 57 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm² - 10 mm², AWG: 20 - 6, Width: 10.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

製品の特長

- ☑ Steel screw connection technology, reliable connection;
- ☑ Equipped with dual-channel bridge wells, circuit connection testing is more flexible;
- ☑ Unique plug-in bridge, high circuit connection efficiency;
- ☑ The box has a baffle to prevent mis-insertion;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Screw type	Slotted screw
Strip length	10~12mm
Conductor cross section solid	0.5~10mm ²
Conductor cross section flexible	0.5~10mm ²
Conductor cross section solid AWG	20~6
screw thread	M4
Tightening torque	1.54N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters

Rated current	65A
---------------	-----

IEC Electrical parameters

Rated voltage (III / 3)	1000V
Rated current (III / 3)	57A
Rated surge voltage	8KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	57mm
End plate width	1.5mm
NS 35/15 Height	64.5mm
length	58.7mm
width	10.2mm
Height	55.5mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94

V0

アクセサリ

Marker

Top marker	/
Side marker	ZB10
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Bridge	DFA10
End cover	D-DC10-TW
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

ビジネスデータ

注文番号	11020000206
パッキングユニット	50
最小注文数量	50
1 個あたりの重量（梱包を含めない）	26.1