


概要

製品情報



WS2.5-QU-PE-100A(H)-11030000194

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm² - 2.5 mm², AWG: 28 - 14, Width: 5 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

製品の特長

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Grounding structure, protection circuit;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length	8~9mm
Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
Conductor cross section solid AWG	28~14

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage

8KV

Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

Dimension

NS 35/7,5 Height

35.45mm

End plate width

2.5mm

NS 35/15 Height

42.95mm

length

75.5mm

width

5mm

Height

32.45mm

Overview

Connection type

Pull back spring connection

Number of rows

1

number of connections

4

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94

V0

アクセサリ

Marker

Top marker

ZB5 / WB5

Side marker

DEK5

Marker support

DTH5-25×5 / DTH5-25×12

Warning cover	EEA2.5
---------------	--------

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.5×3.5
Adjacent jumper (2P)	/
Alternate jumper (2P)	/
Staggered jumper (2P)	/
End cover	D-WS2.5-QU

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11030000194
パッキングユニット	50
最小注文数量	50
1 個あたりの重量（梱包を 含めない）	12.91