


概要

製品情報



DG150-A-12010001050

Up and down transfer terminal, nominal current: 150A, Rated voltage: 1000A, Pitch: 27mm, Color: black, Contact surface: Ni

製品の特長

製品認証

技術データ

製品チャート

3Dモデル

□

Wiring capacity

torque	5.6N.m
Connectable conductor cross section	6~1/0 AWG

Electrical parameters UL

Rated voltage	1000V
Rated current	150A

Item properties

Type of installation	panel
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8

Pitch	27mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials (main class)	PA66+GF
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~120℃
---------------------------------	-----------

アクセサリ

ビジネスデータ

注文番号	12010001050
パッキングユニット	
最小注文数量	
1 個あたりの重量（梱包を 含めない）	