

概要

製品情報



DG46SU-12030000482

Single-layer PCB barrier terminal, Rated current: 30A. Rated voltage (UL) : 300V, Pitch: 9.5mm, Color: black, Contact surface: Sn

製品の特長

- ☒ Screw connection for worldwide use
- ☒ Barrier wiring structure, stable and reliable connection
- ☒ Solder board installation, which can realize the electrical connection between the device and the PCB

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

AWG	22~10AWG
Torque	1.2N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	30A

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Screwdriver	Phillips screwdriver

screw thread	M4
Pitch	9.5mm
Number of potentials	5
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials (main class)	PA66+GF
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Overview

Connection method	screw connection
-------------------	------------------

アクセサリ

ビジネスデータ

注文番号	12030000482
パッキングユニット	180

最小注文数量	
1 個あたりの重量（梱包を 含めない）	0.64