

概要

製品情報



2EDGKNHM-5.08-10020008266

Pluggable terminal blocks, Rated current: 8A. Rated voltage
(III/2) : 400V, pitch: 5.08mm, Color: black, Contact surface : Tin

製品の特長

- ☒ Double-layer compact design
- ☒ PUSH-IN connection technology, fast wiring

製品認証



技術データ

製品チャート

3Dモデル

□

Packaging information

Type of packaging

bag packaging

Connection capacity

Conductor cross section solid

0.2~2.5mm²

Conductor cross section flexible

0.2~1.5mm²

AWG

24~16AWG

Torque

0.2N.m

Strip length

10mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)	300V
Rated current (B)	10A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	400V
Rated current(III/3)	250V
Rated current	8A
Rated current(III/2)	400V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection method	Push-in spring connection
Screwdriver	slotted-phillips screwdriver
screw thread	M2
Pitch	5.08mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66

Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Shell color	Black
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

ビジネスデータ

注文番号	10020008266
パッキングユニット	600
最小注文数量	
1 個あたりの重量（梱包を含めない）	4.21

